



Super Watt **AUTOMATIC** 360 - 450 - 800 - 1500

- Controllo a microprocessore con automatismo di fine carica;
- amperometro per l'indicazione della corrente erogata;
- regolazione della corrente su tutti i modelli;
- collegamenti alla batteria con pinze (in dotazione);
- ritardo inizio carica di 3 secondi ;
- protezione di fine carica max 24 ore e protezione da sovratensione di carica;
- protezione termica a ripristino automatico contro i sovraccarichi;
- protezione elettronica e con fusibile contro inversioni di polarità e cortocircuiti.

- Microprocessor controller for automatic charge;
- ammeter for current indication;
- current regulation in all models;
- battery connections with clamps (equipped);
- 3 seconds delayed start charge;
- over timing charge protection on 24 ours and over voltage charge protection;
- thermic protection with automatic resetting against overloads;
- electronic and fuse protection against polarity inversions and short-circuits.



MODEL	Mains Voltage 50/60Hz 1 ph Volt	Power Watt	Output Voltage Volt	Charge Current Eff. Amp	Charge Current Arith. Amp	Charge Current regulation N°	Nominal Capacity to refer to Ah min-max	Size mm	Weight Kg	Cod N.
Watt Automatic140	230	140	12/24	10/6	7/4	2	15 - 100	250 x 150 x 210	3.9	11010
Watt Automatic 180	230	180	12/24	14/8	9/5.5	2	25 - 140	250 x 150 x 210	4.6	11020
Watt Automatic 220	230	220	12/24	18/10	12/7	4	15 - 180	250 x 150 x 210	5.1	11030
Super Watt Aut. 360	230	360	12/24	24/18	16/12	4	25 - 250	250 x 210 x 280	7.6	11040
Super Watt Aut. 450	230	450	12/24	30/22	20/14	4	30 - 300	250 x 210 x 280	8.2	11050
Super Watt Aut. 800	230	800	12/24	45/36	30/24	4	30 - 450	250 x 230 x 330	11.3	11060
Super Watt Aut. 1500	230	1500	12/24	75/60	50/40	6	30 - 750	250 x 260 x 400	15.4	11070

NEW LINE

Watt **AUTOMATIC** 140 - 180 - 220



Carica batterie automatici per la carica di tutti i tipi di accumulatori al piombo a 12 o 24 V con controllo a microprocessore. Funzione di mantenimento automatica. Ampia regolazione della corrente di carica. Alimentazione 230 Volt monofase. Curva caratteristica di carica "Wa" a corrente decrescente, in accordo con la norma DIN 41774. Costruiti in lamiera verniciata e materiale plastico in policarbonato autoestinguente. Garanzia di due anni su tutti i prodotti.

Automatic battery charger powered by microprocessor controller for all kinds of lead storage batteries of 12 or 24V. Automatic maintenance function. Ample charging current regulation. Single phase 230 Volt power supply. Characteristic "Wa" charge curve at decreasing current, according to DIN 41774 standard. Manufactured in painted plate and plastic material in self-extinguishable polycarbonate. Two years guarantee on all products.

